

Fujitsu recommends Windows 11 Pro.

Data Sheet

Fujitsu Workstation CELSIUS M7010

Bring Your Ideas To Life

Looking for a true workhorse to speed up your creative and engineering workflows? The CELSIUS M7010 is designed to help power users achieve next level of performance and reliability by enabling them design products, build complex 3D models, run simulations, create & visualize digital content. It is a highly expandable VR ready workstation optimized for demanding CAD, CAE and media & entertainment applications.

Performance you can count on

Spectrum of performance due to a wide range of professional grade features

- Powerful Intel® Xeon® Processor W Family
- Support of Windows 11 Pro
- Support of up to 512 GB DDR4 2,933 memory
- Fujitsu SSD PCIe card (up to 2 x 2 TB)

Dual GPU, VR ready workstation

Enjoy a fully immersive and real-time virtual reality experience with low latency at high frame rates

- Intel® vPro® processors with up to 4.6 GHz frequency
- Professional graphics cards up to NVIDIA RTX™ A6000 and AMD Radeon™ Pro WX 3200
- Support for NVIDIA® NVLink™ technology – inter-GPU communication protocol, which makes it perfect for scientific and high-end renderings

Ultimate reliability, usability and innovative design

Quality you can trust

- Built for 24/7 operations with reliable top-quality components
- Intelligent tri-channel thermal management
- Cable-free design and green touchpoints
- Cold-plug technology: Storage accessible via a front disk tray

Robust security

Human centric innovation meets security

- Optional security lock (side door and front access)
- Intrusion detector sensor integrated into the power supply
- USB keyboard with integrated PalmSecure™: Easy log-on with the help of your palm veins frame rates



Components

	CELSIUS M7010 (S26361-K1507-V165)	CELSIUS M7010power (S26361-K1507-V265)
Processor	Intel vPro® technology	
Operating systems		
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 11 Pro for business.	
Operating system compatible	FREE Upgrade to Windows 11* *Upgrade timing may vary by device. Features and app availability may vary by region. Certain features require specific hardware (see aka.ms/windows11-spec).	
Operating system notes	Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server Windows 11 requires for first device setup: - Internet connectivity - Microsoft account for Home editions or organizational account (e.g. ADD) for Pro editions After product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, depending on extension of hardware services through warranty top ups. For more details please visit our Fujitsu Service Statement under https://support.ts.fujitsu.com/IndexProdSupport.asp?lng=com&OpenTab=	
	CELSIUS M7010 (S26361-K1507-V165)	CELSIUS M7010power (S26361-K1507-V265)
Memory modules	8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,933 MT/s 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s 32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s 64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s	
	CELSIUS M7010 (S26361-K1507-V165)	CELSIUS M7010power (S26361-K1507-V265)
Graphics	High-end 3D: NVIDIA® Quadro® RTX 4000, 8 GB, PCIe x16, 3 x DisplayPort, 1 x Virtual Link Entry 3D: NVIDIA® T1000, 4 GB, PCIe x16, 4 x miniDP Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4 x miniDP Others: MiniDP to DP Adapter Cable Others: DP to DVI-D (single link) Adapter Cable	Ultra-high-end 3D: NVIDIA® RTX™ A6000, 48 GB, PCIe x16, 4 x DisplayPort Ultra-high-end 3D: NVIDIA® RTX™ A5000, 24 GB, PCIe x16, 4 x DisplayPort High-end 3D: NVIDIA® RTX™ A4500, 20 GB, PCIe x16, 4 x DisplayPort High-end 3D: NVIDIA® Quadro® RTX 4000, 8 GB, PCIe x16, 3 x DisplayPort, 1 x Virtual Link Entry 3D: NVIDIA® T1000, 4 GB, PCIe x16, 4 x miniDP Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4 x miniDP Others: MiniDP to DP Adapter Cable Others: DP to DVI-D (single link) Adapter Cable
	CELSIUS M7010 (S26361-K1507-V165)	CELSIUS M7010power (S26361-K1507-V265)
Hard disk drive	HDD SATA III, 7,200 rpm, 1,000 GB, 2.5-inch, business critical HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 2,000 GB, 2.5-inch, business critical HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 4,000 GB, 3.5-inch, business critical SSD PCIe, 1x 2048 GB M.2 NVMe Highend card SSD PCIe, 1x 512 GB M.2 NVMe Highend card SSD PCIe, 1x 1024 GB M.2 NVMe Highend card SSD PCIe, 2048 GB M.2 NVMe Highend module SSD PCIe, 256 GB M.2 NVMe Highend module SSD PCIe, 2x 1024 GB M.2 NVMe Highend card SSD PCIe, 2x 2048 GB M.2 NVMe Highend card SSD PCIe, 2x 512 GB M.2 NVMe Highend card SSD SATA III, 960 GB High Endurance, 1.5DWDP, 2.5-inch	
Mass storage 3.5 inch size	HDD SATA III, 7,200 rpm, 8000 GB, 3.5-inch, business critical	

Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. 24/7 ready (Business Critical HDDs or SAS HDDs or High Endurance SSDs required) Up to 20 GB of HDD space is reserved for system recovery SED (Self-Encrypting Drive) SSD (Solid State Disk)	
	CELSIUS M7010 (S26361-K1507-V165)	CELSIUS M7010power (S26361-K1507-V265)
Optical drive	MultiCard Reader 24in1 USB 2.0 3.5", USB 2.0 DVD Super Multi, SATA DVD Super Multi ultra slim (tray), SATA BD Triple Writer SATA ultra slim (tray), SATA	
SCSI / SAS Controller	Intel VROC HW key Standard M.2	
	CELSIUS M7010 (S26361-K1507-V165)	CELSIUS M7010power (S26361-K1507-V265)
Interfaces add on cards / components	WLAN 802.11ac (2x2) PCIe x1 and BT 5, SRD 5.8GHz (dedicated regions only) PLAN EP X550-T2 2x10GBASE-T Dual serial card PCIe x1	
	CELSIUS M7010 (S26361-K1507-V165)	CELSIUS M7010power (S26361-K1507-V265)

Base unit

Base unit	CELSIUS M7010 (S26361-K1507-V165)	CELSIUS M7010power (S26361-K1507-V265)
Mainboard		
Mainboard type	D3498-A2	
Formfactor	extended ATX	
Chipset	Intel® C422	
Processor socket	Socket R4	
Processor quantity maximum	1	
Supported capacity RAM (max.)	512 GB	
Memory slots	8 DIMM (DDR4) ECC	
Memory frequency	2,933 MT/s	
Memory notes	4 memory channels supporting up to 2 DIMMs per channel. For quad channel, a minimum of 4 memory modules have to be ordered and the capacity per channel has to be the same. DDR4 2,933MHz may be clocked down to 2,666 or 2,400 or 2,133 depending on the processor.	
LAN	10/100/1,000 MBit/s Intel® I219LM	
BIOS version	AMI Aptio V	
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)	
Audio type	On board	
Audio codec	Realtek ALC671	
Audio features	High Definition Audio	
I/O controller on board		
Serial ATA total	8	
thereof SATA III	8	
thereof eSATA		
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10	
Interfaces		
Audio: in (rear)	1	1
Audio: out (rear)	1	1

Interfaces

Audio: in	1	1
Audio: out	1	1
Internal speakers	1	1
USB 2.0 total	2 optional via front panel	2 optional via front panel
USB 3.1 Gen1 (USB 3.0) total	6	6
USB 3.1 Gen2 total	2 optional via front panel	2 optional via front panel
USB front	2x USB 2.0; 2x USB 3.1 (Gen1); optional: 2x USB 3.1 Type-C (Gen2) instead of 2x USB 2.0	2x USB 2.0; 2x USB 3.1 (Gen1); optional: 2x USB 3.1 Type-C (Gen2) instead of 2x USB 2.0
USB rear	6	6
USB internal	3, thereof 1 type A	3, thereof 1 type A
Ethernet (RJ-45)	1	1
eSATA	1 (optional)	1 (optional)
Interface Module notes	Anytime USB charge functionality	Anytime USB charge functionality

Drive bays

Drive bays total	7
2.5-inch internal bays	4
3.5-inch internal bays	4
3.5-inch external bays	1
5.25-inch external bays	1
Drive bay notes	Total 4x 3.5-inch/2.5-inch Disk Tray front accessible (with Cold-plug access)
M.2-2280	1 x on mainboard (for PCIe SSD modules)

Slots

PCI-Express 3.0 x1	2 x (340 mm / 13.39 inch) Full height	
PCI-Express 3.0 x4	2 x (340 mm / 13.39 inch) Full height	
PCI-Express 3.0 x8	1 x (200 mm) Full height	
PCI-Express 3.0 x16	2 x (340 mm / 13.39 inch) Full height	
Base unit	CELSIUS M7010 (S26361-K1507-V165)	CELSIUS M7010power (S26361-K1507-V265)

Electrical values

Power consumption note	225 W depending on configuration	400 W depending on configuration
Rated voltage range	100 V - 240 V	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz	47 Hz - 63 Hz
Max. output of single power supply	450 W up to 90% efficiency	Continuous main output power - 800 W (up to 90% efficiency) Peak main output power - 1080 W for max. duration of 10ms
Power factor correction/active power	active	active
Power supply output	2 graphics power rails (on Mainboard)	2 graphics power rails (on Mainboard)
Base unit	CELSIUS M7010 (S26361-K1507-V165)	CELSIUS M7010power (S26361-K1507-V265)

Noise for standard configuration (HDD, ODD)

Related Processors for noise	140W Thermal Design Power (TDP) Processor
Standard noise emission	According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.6 B / 20 dB(A) Bystander position
Standard noise operation mode: CPU 90% load	3.7 B / 20 dB(A) Bystander position
Standard noise operation mode: HDD load	3.5 B / 19 dB(A) Bystander position

Noise for standard configuration (HDD, ODD)

Standard noise operation mode: Idle mode	3.5 B / 19 dB(A) Bystander position
Standard noise operation mode: ODD load	4.5 B / 28 dB(A) Bystander position
Standard noise operation mode: Office applications 2.0	3.7 B / 21 dB(A) Bystander position

Dimensions / Weight / Environmental

Dimensions (W x D x H)	176 x 500 x 433 mm 6.9 x 19.7 x 17.1 inch
Operating position	Vertical / horizontal
Weight	approx. 18 kg
Weight (lbs)	approx. 39.67 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	CELSIUS M7010	CELSIUS M7010power
Model	CM17	
Germany	GS depending on configuration	
Europe	CE	
USA/Canada	FCC Class B cCSAus	
Global	RoHS (EU & China) Microsoft Operating Systems (HCT / HCL entry / WHQL) WEEE (Waste electrical and electronic equipment)	
Compliance notes	Product Name maybe followed by suffixes	
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	

Additional Software

Additional software (preinstalled)	McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.

Supported ISV Applications	AllPlan GmbH - AllPlan ¹ Dassault Systèmes® CATIA™ ¹ Dassault Systèmes® SOLIDWORKS® ¹ PTC® Creo® ¹ Siemens Digital Industries - NX ¹ Siemens Digital Industries - Solid Edge ¹ Adobe® After Effects® ² Adobe® Dreamweaver® ² Adobe® Illustrator® ² Adobe® InDesign® ² Adobe® Photoshop® ² Adobe® Premiere® Pro ² Autodesk® AutoCAD® ² Autodesk® Inventor® ² Autodesk® Maya® ² Autodesk® Revit® ² Autodesk® VRED® ² Bentley OpenComms™ Designer ²
Supported ISV Applications (notes)	¹ System certification (for selected configurations) ² ISV support given via usage of certified graphic card Please refer to the ISV documentation (https://sp.ts.fujitsu.com/dmsp/Publications/public/wp-FUJITSU-Workstation-CELSIUS-ISV-overview.pdf) for further details and current status on system ISV certifications.
Base unit	CELSIUS M7010 (S26361-K1507-V165) CELSIUS M7010power (S26361-K1507-V265)
Security	
Physical Security	Kensington Lock support Eye for padlock Intrusion switch Integrated cabinet lock (optional)
System and BIOS Security	Embedded security (TPM 2.0) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)
Workplace Embedded Tools	Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional)
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.
Manageability	
Manageability technology	DeskUpdate Driver management iAMT 11.6 (depending on processor) PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management

Manageability

DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
Manageability link	https://www.fujitsu.com/global/products/computing/pc/manageability/

Miscellaneous

	Rack mountable (4U)
Spare part availability	5 years

Packaging information

Packaging notes	printed user documentation is bleached in chlorine free process
-----------------	---

Warranty

Warranty type	Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.

Product Support - the perfect extension

Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/
-----------------	---

Recommended Accessories

SpaceMouse Pro



Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:
S26381-K459-L100

More information

Fujitsu products, solutions & services

In addition to the Fujitsu Workstation CELSIUS M7010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about the Fujitsu Workstation CELSIUS M7010, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2023 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2023-11-27 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>
Copyright 2023 Fujitsu Technology Solutions GmbH