

Fujitsu recommends Windows 11 Pro.

# Data Sheet

## Fujitsu Workstation CELSIUS W5011

### VR Ready CAD Powerhouse

If you thought you would need to sacrifice performance, expandability, price or energy efficiency in a micro tower design – think again. The Fujitsu CELSIUS W5011 desktop workstation goes far and beyond with its innovative design, featuring maximum graphic performance and dual slot full-length graphics card support. With its best-in-class low-noise emissions, it enables a quiet and efficient working environment.

No compromise in terms of performance, expandability and price  
Designed with CAD customers in mind: performance, reliability and great flexibility - at an affordable price

- Choose between the latest 11th generation Intel® Core™ processors or the powerful Intel® Xeon® W-1300 processor family
- Support of Windows 11 Pro
- Up to 128 GB DDR4 3,200 MT/s memory (incl. ECC)
- Dual slot full-length graphics cards (up to NVIDIA RTX™ A5000)
- Broad choice of processors and professional graphics cards
- Support of 24/7 operation with reliable high-endurance and business critical drives

VR-ready desktop workstation

Innovative space-saving design - made in Europe

- 21 liter desktop micro tower workstation
- Powered by advanced VR-ready graphics cards
- Optimized thermal management and cooling solutions
- Enjoy a silent workplace environment thanks to low noise emission

The smartest micro tower workstation

Ultimate usability, reliability and ease of use

- Clean, clutter-free interiors with less cables and cold-plug technology for HDDs inside
- Tool-less access to components for easy access and upgrade
- High-speed data transfer with SSD NVMe
- Supports massive amount of data storage with 4 storage slots

Multiple application scenarios

Ideal for 3D CAD, CAE, design, multimedia, visualization and manufacturing

- Supports graphics-accelerated applications
- Advanced CPUs in combination with flash storage for best application performance
- Up to 8 monitors with the NVIDIA® Mosaic™ technology



# Components

	CELSIUS W5011	CELSIUS W5011 ESTAR
<b>Processor</b>	Intel® vPro® Platform with all Intel® Xeon® processors Intel® vPro® Platform Logo with Intel® Core™ i5 10505, Intel® Core™ i5-11500, Intel® Core™ i5-11600, Intel® Core™ i7 and Intel® Core™ i9 processors *with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on workload and other variables)	
Operating system preinstalled		
Operating system pre-installed	Windows 11 Home Windows 10 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business.	
Operating system compatible	FREE Upgrade to Windows 11* *Upgrade timing may vary by device. Features and app availability may vary by region. Certain features require specific hardware (see aka.ms/windows11-spec).	
Operating system notes	Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server Windows 11 requires for first device setup: - Internet connectivity - Microsoft account for Home editions or organizational account (e.g. ADD) for Pro editions After product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, depending on extension of hardware services through warranty top ups. For more details please visit our Fujitsu Service Statement under <a href="https://support.ts.fujitsu.com/IndexProdSupport.asp?lng=com&amp;OpenTab=">https://support.ts.fujitsu.com/IndexProdSupport.asp?lng=com&amp;OpenTab=</a>	
	CELSIUS W5011	CELSIUS W5011 ESTAR
<b>Memory modules</b>		
	CELSIUS W5011	CELSIUS W5011 ESTAR
<b>Graphics</b>	Ultra-high-end 3D: NVIDIA® RTX™ A5000, 24 GB, PCIe x16, 4 x DisplayPort High-end 3D: NVIDIA® RTX™ A4000, 16 GB, PCIe x16, 4 x DisplayPort High-end 3D: NVIDIA® Quadro RTX™ 4000, 8 GB, PCIe x16, 3 x DisplayPort, 1 x Virtual Link Midrange 3D: NVIDIA® RTX™ A2000, 12 GB, PCIe x16, 4 x DisplayPort Midrange 3D: NVIDIA® Quadro® P2200, 5 GB, PCIe x16, 4 x DisplayPort Entry 3D: NVIDIA® T1000, 8 GB, PCIe x16, 4 x miniDP Entry 3D: NVIDIA® T1000, 4 GB, PCIe x16, 4 x miniDP Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4 x miniDP Others: MiniDP to DP Adapter Cable	Midrange 3D: NVIDIA® Quadro® P2200, 5 GB, PCIe x16, 4 x DisplayPort Entry 3D: NVIDIA® T1000, 4 GB, PCIe x16, 4 x miniDP Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4 x miniDP Others: MiniDP to DP Adapter Cable
	CELSIUS W5011	CELSIUS W5011 ESTAR
	CELSIUS W5011	CELSIUS W5011 ESTAR
<b>Mass storage 2.5 inch size</b>	SSD SATA III, 960 GB High Endurance, 1.5DWDP, 2.5-inch	
<b>Mass storage 3.5 inch size</b>	HDD SATA III, 7,200 rpm, 2000 GB, 3.5-inch HDD SATA III, 7,200 rpm, 4000 GB, 3.5-inch, business critical HDD SATA III, 7,200 rpm, 8000 GB, 3.5-inch, business critical	
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive)	

	CELSIUS W5011	CELSIUS W5011 ESTAR
<b>Optical drive</b>	DVD Super Multi, SATA DVD Super Multi ultra slim (tray), SATA BD Triple Writer SATA ultra slim (tray), SATA MultiCard Reader 15in1 USB 3.0 3.5"; USB 3.0	DVD Super Multi ultra slim (tray), SATA BD Triple Writer SATA ultra slim (tray), SATA MultiCard Reader 15in1 USB 3.0 3.5"; USB 3.0
	CELSIUS W5011	CELSIUS W5011 ESTAR
<b>Interfaces add on cards / components</b>	2.5 Gigabit Ethernet PCIe x1	
<b>Drives</b>	SD-Card 4.0 reader in front	
	CELSIUS W5011	CELSIUS W5011 ESTAR
<b>Component notes</b>	The listed product components and optional functions are not available in all region/countries	The listed product components and optional functions are not available in all region/countries; Energy Star certification only with Windows operating system

## Base unit

Base unit	CELSIUS W5011	CELSIUS W5011 ESTAR
<b>Mainboard</b>		
Mainboard type	D3917	D3917
Formfactor	proprietary	proprietary
Chipset	Intel® W580	Intel® W580
Processor socket	LGA 1200	LGA 1200
Processor quantity maximum	1	1
Supported capacity RAM (max.)	128 GB	128 GB
Memory slots	DIMM (DDR4) ECC/non-ECC	DIMM (DDR4) ECC/non-ECC
Memory frequency	3,200 MT/s	3,200 MT/s
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 3200 MT/s may be clocked down to 2933/2400 MT/s depending on processor and memory configuration	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 3200 MT/s may be clocked down to 2933/2400 MT/s depending on processor and memory configuration
LAN	10/100/1,000 MBit/s Intel® I219LM Optional LAN connectors: LAN 2.5GB Ethernet (Intel 225LM)	10/100/1,000 MBit/s Intel® I219LM
Integrated WLAN	optional; Intel® Wi-Fi 6 AX210 (2x2/160) Gig+ and Bluetooth 5.2	optional; Intel® Wi-Fi 6 AX210 (2x2/160) Gig+ and Bluetooth 5.2
BIOS version	AMI Aptio V UEFI Specification 2.6	AMI Aptio V UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board	On board
Audio codec	Realtek ALC623	Realtek ALC623
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound
<b>I/O controller on board</b>		
Serial ATA total	6	
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI SATA RAID (0, 1, 5, 10) Support	

**FPC64032GK CELSIUS W5011**

Audio: line-in	1	1
Audio: line-out	1	1
Front audio: headset	1	1
USB 2.0 total	4	4
USB 3.2 Gen1 (5 Gbps) total	3	3
USB 3.2 Gen2 (10 Gbps) total	3 and 1 optional	3 and 1 optional
USB 3.2 Gen2x2 (20 Gbps) total	1	1
USB front	2x USB 2.0 2x USB 3.2 Gen 2 1x USB 3.2 Gen 2x2 Type-C (supports up to 15W)	2x USB 2.0 2x USB 3.2 Gen 2 1x USB 3.2 Gen 2x2 Type-C (supports up to 15W)
USB rear	2x USB 2.0 3x USB 3.2 Gen 1 1x USB 3.2 Gen 2 optional: additional 1x USB 3.2 Gen 2 Type-C (supports DisplayPort 1.4 and power delivery (PD) up to 15W or 60W (occupies PCIe x16 slot)	2x USB 2.0 3x USB 3.2 Gen 1 1x USB 3.2 Gen 2 optional: additional 1x USB 3.2 Gen 2 Type-C (supports DisplayPort 1.4 and power delivery (PD) up to 15W or 60W (occupies PCIe x16 slot)
USB internal	1x USB 2.0 Type A	1x USB 2.0 Type A
VGA	no	no
DisplayPort	2 (third DP optional)	2 (third DP optional)
DVI	no	no
Serial (RS-232)	1 (optional serial port (9pin, 16 byte FIFO, 16550 compatible))	1 (optional serial port (9pin, 16 byte FIFO, 16550 compatible))
HDMI	optional	optional
Ethernet (RJ-45)	1	1
Interface Module notes	Anytime USB charge functionality	Anytime USB charge functionality

**Input device / components**

Input devices (optional)	Keyboard Mouse	
Drive bays total	6	6
2.5-inch internal bays	1	1
3.5-inch internal bays	2	2
3.5-inch external bays	1	1
5.25-inch external bays	2	2
Drive bay notes	5,25" bays: one bay in HH format, one bay for slim optical disc drive only; internal 3.5" bays: 3.5" drive (screwless) or 2.5" drive (screws; optional screwless)	5,25" bays: one bay in HH format, one bay for slim optical disc drive only; internal 3.5" bays: 3.5" drive (screwless) or 2.5" drive (screws; optional screwless)
M.2-2280	2 x on mainboard for SSD NVMe: 1x PCIe 4.0 x4; up to 64Gbit/s; only with 11th generation CPUs 1x PCIe 3.0 x4; up to 32Gbit/s	2 x on mainboard for SSD NVMe: 1x PCIe 4.0 x4; up to 64Gbit/s; support with 11th generation CPUs only 1x PCIe 3.0 x4; up to 32Gbit/s

**Slots**

PCI-Express 3.0 x1	2 x (110 mm and 270 mm / 4.33 inch and 10.63 inch) Full height
PCI-Express 3.0 x4 (mech. x16)	1 x (270 mm / 10.63 inch) Full height
PCI-Express 4.0 x16	1 x (270 mm / 10.63 inch) Full height
M.2-2230	on mainboard for WLAN/Bluetooth module

**Graphics on board**

Graphics brand name	Intel® UHD Graphics P750, Intel® UHD Graphics 750, Intel® UHD Graphics 730, Intel® UHD Graphics 630
Shared video memory	Up to half size of total system memory
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel
TFT resolution (HDMI)	Up to 4,096 x 2,160 @ 60 Hz

## Graphics on board

Graphics features	<p>Support for up to three independent displays</p> <p>DirectX® 12</p> <p>HDCP support</p> <p>OpenCL™ 2.1</p> <p>OpenGL® 4.5</p> <p>For multi monitoring mode, graphics card and integrated graphics run in parallel</p> <p>DisplayPort interface supports Ver. 1.4 incl. Multi-Stream</p> <p>Digital audio formats are supported, including Dolby Digital Plus (7.1 channels)</p> <p>DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not included)</p> <p>System provides one connector to be used for LAN or graphics</p> <p>Optional graphics connectors:</p> <p>HDMI™ 2.0b</p> <p>DisplayPort™ 1.4a</p> <p>USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W)</p> <p>USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 60W. Occupies PCIe x16 slot)</p>
Graphics notes	<p>up to 1 GB dedicated video memory (main memory owned and locked for graphics use)</p> <p>Tested resolutions, depending on display type additional resolutions and frequencies possible</p> <p>Shared memory depending on main memory size and operating system</p> <p>Resolution (color depth up to 32 Bit/pixel)</p> <p>For TFT we recommend using 60Hz</p>
Base unit	<p>CELSIUS W5011</p> <p>CELSIUS W5011 ESTAR</p>

## Electrical values

Power efficiency note	<p>Power supply efficiency in % at 10% / 20% / 50% / 100% load</p> <p>80Plus PLATINUM 680W:</p> <p>for 230V ; 89/92/93/92</p> <p>for 115V ; 88/91/92/90</p> <p>80Plus PLATINUM 300W:</p> <p>for 230V ; 88/92/94/93</p> <p>for 115V ; 87/91/92/91</p>
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	300W or 680 W (depending on PSU)
Power factor correction/active power	active
Power supply output	Power supply PLATINUM 680W: 2 graphics power rails (6 pin- and 8 pin connectors)
Base unit	<p>CELSIUS W5011</p> <p>CELSIUS W5011 ESTAR</p>

## Noise emission

Standard noise emission	According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level L <sub>wad</sub> (in B) / Workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A))
Standard noise operation mode: CPU 50% load	<p>Bystander; Operator position for 300W PSU</p> <p>Xeon W-1350, Nvidia T1000, 16GB, SSD M.2:</p> <p>3.1 B / 17 dB(A) ; 21 dB(A)</p> <p>Core i7-11700, Nvidia T400, 8GB, SSD M.2:</p> <p>2.9 B / 16 dB(A); 19 dB(A)</p>
Standard noise operation mode: HDD load	<p>Bystander; Operator position for 300W PSU</p> <p>Xeon W-1350, Nvidia T1000, 16GB, SSD M.2:</p> <p>3.1 B / 17 dB(A); 21 dB(A)</p>
Standard noise operation mode: Idle mode	<p>Core i7-11700, Nvidia T400, 8GB, SSD M.2:</p> <p>2.9 B / 16 dB(A); 19 dB(A)</p>
Standard noise operation mode: ODD load	<p>Bystander; Operator position for 300W PSU</p> <p>Xeon W-1350, Nvidia T1000, 16GB, SSD M.2:</p> <p>4.7 B / 33 dB(A); 39 dB(A)</p> <p>Core i7-11700, Nvidia T400, 8GB, SSD M.2:</p> <p>4.8 B / 33 dB(A); 39 dB(A)</p>

**Noise emission**

Standard noise operation mode: Office applications 2.0	Bystander; Operator position for 300W PSU Xeon W-1350, Nvida T1000, 16GB, SSD M.2: 3.1 B / 17 dB(A); 21 dB(A) Core i7-11700, Nvida T400, 8GB, SSD M.2: 2.9 B / 16 dB(A); 19 dB(A)	
Dimension with stand (W x D x H)		
Dimensions (W x D x H)	180 x 304 x 375 mm 7.09 x 11.97 x 14.76 inch	
Operating position	Vertical	
Weight	approx. 10 kg	
Weight (lbs)	approx. 22.05 lbs	
Weight notes	Actual weight may vary depending on configuration	
Operating ambient temperature	10 - 35 °C (50 - 95 °F)	
Operating relative humidity	5 - 85 % (relative humidity)	
Product	CELSIUS W5011	CELSIUS W5011 ESTAR
Model	MI7W	
Germany	GS TÜV NRTL	
Europe	CE	
USA/Canada	FCC Class B cTUVus	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) Microsoft Secured-core PC certification (for selected configurations)	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) Microsoft Secured-core PC certification (for selected configurations) ENERGY STAR® 8.0 EPEAT® Gold (dedicated regions)
Compliance link	<a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>	

**Additional Software**

Additional software (preinstalled)	McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office. Purchase and activation only in the region in which it was acquired.)
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.

Supported ISV Applications	AllPlan GmbH - AllPlan <sup>1</sup> Dassault Systèmes® CATIA™ <sup>1</sup> Dassault Systèmes® SOLIDWORKS® <sup>1</sup> PTC® Creo® <sup>1</sup> Siemens Digital Industries - NX <sup>1</sup> Siemens Digital Industries - Solid Edge <sup>1</sup> Adobe® After Effects® <sup>2</sup> Adobe® Dreamweaver® <sup>2</sup> Adobe® Illustrator® <sup>2</sup> Adobe® InDesign® <sup>2</sup> Adobe® Photoshop® <sup>2</sup> Adobe® Premiere® Pro <sup>2</sup> Autodesk® AutoCAD® <sup>2</sup> Autodesk® Inventor® <sup>2</sup> Autodesk® Maya® <sup>2</sup> Autodesk® Revit® <sup>2</sup> Autodesk® VRED® <sup>2</sup> Bentley OpenComms™ Designer <sup>2</sup>
Supported ISV Applications (notes)	<sup>1</sup> System certification (for selected configurations) <sup>2</sup> ISV support given via usage of certified graphic card Please refer to the ISV documentation ( <a href="https://sp.ts.fujitsu.com/dmsp/Publications/public/wp-FUJITSU-Workstation-CELSIUS-ISV-overview.pdf">https://sp.ts.fujitsu.com/dmsp/Publications/public/wp-FUJITSU-Workstation-CELSIUS-ISV-overview.pdf</a> ) for further details and current status on system ISV certifications.
Base unit	CELSIUS W5011 <span style="float: right;">CELSIUS W5011 ESTAR</span>
<b>Security</b>	
Physical Security	Kensington Lock support Eye for padlock Integrated cabinet lock (optional) Cable Cover (optional; covers and secures the ports and cables on rear side)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby ready (for configurations with Gen4 NVMe SSD and w/o PCIe cards) Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)
<b>Manageability</b>	
<b>Packaging information</b>	
Packaging dimension (mm)	537 x 298 x 505 mm
Packaging dimension (inch)	21.14 x 11.73 x 19.88 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1224 g
Material - Weight (lbs) Carton	2.7 lbs
Material - Weight (g) EPS / PS	256 g
Material - Weight (lbs) EPS / PS	0.56 lbs
Material - Weight (g) PE	25 g
Material - Weight (lbs) PE	0.06 lbs
Packaging notes	printed user documentation is bleached in chlorine free process; Bulk packaging for projects (optional)
<b>Warranty</b>	
Warranty period	3 years (depending on country)
Warranty type	Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations)
Warranty Terms & Conditions	<a href="http://www.fujitsu.com/warranty">http://www.fujitsu.com/warranty</a>

**Warranty**

Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a> free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.
-------------------	--

**Product Support - the perfect extension**

Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	at least 5 years after shipment, for details see <a href="https://support.ts.fujitsu.com/">https://support.ts.fujitsu.com/</a>
Service Weblink	<a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a>

## Recommended Accessories

## Blue LED Mouse M960



The Blue LED Mouse M960 comes in a slim design with proven Fujitsu engineering quality. The track on glass Blue LED sensor enables ultra precise switchable resolution at 1,000, 1,600 and 2,000 dpi. Blue LED Mouse M960 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.

Order Code:  
S26381-K470-L100

## SpaceMouse Pro



Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:  
S26381-K459-L100

## Keyboard KB955



The KB955 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB955 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K955-L4\*\* (\*\*:  
Country specific variation)

# More information

## Fujitsu products, solutions & services

In addition to the Fujitsu Workstation CELSIUS W5011, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about the Fujitsu Workstation CELSIUS W5011, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/emeia/CELSIUS](http://www.fujitsu.com/emeia/CELSIUS)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>  
Copyright 2024 Fujitsu Technology Solutions GmbH

## Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

## Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com](http://www.fujitsu.com)  
2024-04-06 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <https://www.fujitsu.com/global/about/resources/terms/>  
Copyright 2024 Fujitsu Technology Solutions GmbH