Fujitsu recommends Windows 11 Pro.

FUJITSU

Data Sheet Fujitsu Desktop ESPRIMO D6012

Small form factor PC in a more compact and space-saving design

The Fujitsu ESPRIMO D6012 is a high performance, secure small form factor Desktop PC with good expandability and good price performance ratio. Faster operations and a new housing helps in space saving to create the perfect working desk. The 80Plus GOLD and 80Plus PLATINUM power supply helps to reduce environmental impact and energy bills.

Latest Intel® chipset technology and higher memory speed Good performance ensures faster operations and lower system response time Intel® B660 chipset with higher memory frequency of 3,200 MT/s

Housing provides good expandability

- Space saving design
- 1x low profile (LP)
- Space saving in width and depth with new 8.3 liters volume

Good connectivity

- Be flexible and stay productive in a hyper-connected world
- 4x USB Type-A ports, USB Type-C and audio port in front for easy access

High security with integrated options

Designed to protect data and hardware components against manipulation and theft

- Cable cover and integrated cabinet lock with master key option, EraseDisk software
- Hole for pad lock and Kensington as standard for security
- Embedded security with TPM 2.0, EraseDisk, Workplace Protect

Low power consumption and environmental impact

Reduced environmental impact and reduced energy bills

- 80Plus GOLD and 80Plus PLATINUM power supply efficiency with monitor outlet
- Sum of post-consumer recycled content for plastic per weight is 61% (18% are from ITE derived post-consumer material and 43% are any other post-consumer material)









Components

| | ESPRIMO D6012 | ESPRIMO D6012 ESTAR |
|--------------------------------|---|--|
| Processor | | |
| | *with Intel® Turbo Boost Technology 2.0 (clock speed and variables) | performance will vary depending on workload and other |
| | **with Intel® Turbo Boost Max Technology 3.0 (clock speed other variables) | d and performance will vary depending on workload and |
| Operating systems | | |
| Operating system pre-installed | Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home Windows 10 Pro. Fujitsu recommends Windows 11 Pro for business. | |
| Operating system compatible | Certified for Red Hat© Enterprise Linux | Dusiness. |
| Operating system notes | Certified for Ked Hat© Enterprise Linux Windows 11 requires for first device setup: - Internet connectivity - Microsoft account for Home editions or organizational account (e.g. ADD) for Pro editions After product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, depending on extension of hardware services through warranty top ups. For more details please visit our Fujitsu Service Statement under https://support.ts.fujitsu.com/IndexProdSupport. asp?lng=com&OpenTab= The use of Windows Operating System is subject to acceptance of the End User License Agreement of Microsoft as applicable under the relevant Microsoft program. ESPRIMO D6012 ESPRIMO D6012 ESTAR | |
| Memory modules | | |
| | ESPRIMO D6012 | ESPRIMO D6012 ESTAR |
| Graphics | | |
| Hard disk notes | One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive) | |
| | ESPRIMO D6012 | ESPRIMO D6012 ESTAR |
| Optical drive | | |
| | ESPRIMO D6012 | ESPRIMO D6012 ESTAR |
| LAN Notes | WI-FI 6E: The device does not operate in 6GHz band in all countries, due to national regulations. Bluetooth 5.2: Bluetooth® 5.2 operation requires Microsoft OS support. Until Microsoft OS support is available, Bluetooth® 5.2 will function as Bluetooth® 5.1 or lower | |
| | ESPRIMO D6012 | ESPRIMO D6012 ESTAR |
| Component notes | The listed product components and optional functions ar not available in all region/countries | The listed product components and optional functions ar not available in all region/countries; Energy Star certification only with Windows operating system Base unit for TCO Certified generation 9 |

Base unit

| | ESPRIMO D6012 ESTAR |
|-------------------------|---------------------|
| | |
| D4023-A1 | |
| proprietary | |
| Intel [®] B660 | |
| | proprietary |

| Mainboard | | | |
|--------------------------------|--|---|--|
| Processor socket | LGA1700 | | |
| Processor quantity maximum | 1 | | |
| Supported capacity RAM (max.) | 128 GB | | |
| Memory slots | 4 DIMM (DDR4) | | |
| Memory frequency | 3,200 MT/s | | |
| Memory notes | Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 3200 MT/s may be clocked down to 2933/2400 MT/s depending on processor and memory configuration | | |
| AN | 10/100/1,000 MBit/s Realtek RTL8111H | | |
| ntegrated WLAN | optional | | |
| BIOS version | AMI Aptio V UEFI Specification 2.8 | | |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) | | |
| Audio type | On board | | |
| Audio codec | Realtek ALC897 | | |
| Audio features | Internal speaker supports audio playback, High Definition | audio, 5.1 surround sound | |
| /O controller on board | | | |
| Serial ATA total | 4 | | |
| Controller functions | Serial ATA III (6 Gbit) NCQ AHCI SATA RAID Support | | |
| nterfaces | | | |
| Audio: line-in | 1 | 1 | |
| Audio: line-out | 1 | 1 | |
| Front audio: headset | 1 | 1 | |
| JSB front | 2x USB 2.0; 2x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-C (supports up to 15W) | 2x USB 2.0; 2x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-C (supports up to 15W | |
| USB rear | 2x USB 2.0; 2x USB 3.2 Gen 1 (5 Gbps) Type-A | 2x USB 2.0; 2x USB 3.2 Gen 1 (5 Gbps) Type-A | |
| JSB internal | 1x USB 2.0 | 1x USB 2.0 | |
| DisplayPort | 2 (DisplayPort 1.4; DP++) | 2 (DisplayPort 1.4; DP++) | |
| Ethernet (RJ-45) | 1 | 1 | |
| nterface Module notes | Anytime USB charge functionality | Anytime USB charge functionality | |
| Kensington Lock support | 1 | 1 | |
| nput device / components | | | |
| Input devices (optional) | Keyboard Mouse | | |
| Drive bays | | | |
| Drive bays total | 3 | | |
| 2.5-inch internal bays | 1 | | |
| 5.25-inch external bays | 1 | | |
| Drive bay notes | optional: 1x internal 3.5" bay (screwless) can be used via adapter for 1x or 2x 2.5" drives (screwless); 5.25" bay: for slim optical disc drive only; | | |
| W.2-2280 | 1 x on mainboard for SSD NVMe (PCle 4.0 x4; up to 64Gbit/s) | | |
| Slots | | | |
| PCI-Express 3.0 x4 (mech. x16) | 1 x (150 mm / 5.91 inch) | | |
| W.2-2230 | on mainboard for WLAN module | | |
| | | | |
| Graphics on board | | Intel® UHD Graphics 770, Intel® UHD Graphics 730, Intel® UHD Graphics 710 | |

| Graphics on board | | |
|---|---|--|
| Shared video memory | Up to half size of total system memory | |
| TFT resolution (DisplayPort) | Up to 4,096 x 2,304 pixel | |
| Graphics features | Support for up to four independent displays DirectX® 12.1 HDCP support OpenGL 3.0 OpenGL ® 4.6 Vulkan™ For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) | |
| Base unit | ESPRIMO D6012 ESTAR | |
| Electrical values | | |
| Power efficiency note | Power supply efficiency in % at 10% / 20% / 50% / 100% load 80Plus GOLD: for 230V ; 87/90/92/91 for 115V ; 86/89/91/88 80Plus PLATINUM: for 230V ; 88/92/94/93 for 115V ; 87/91/92/91 | |
| Rated voltage range | 100 V - 240 V | |
| Rated frequency range | 50 Hz - 60 Hz | |
| Operating voltage range | 90 V - 264 V | |
| Dperating line frequency range | 47 Hz - 63 Hz | |
| Max. output of single power supply | GOLD: 280W; PLATINUM: 300 W | |
| Power factor correction/active power | active | |
| Nonitor outlet | Switched for PLATINUM power supply | |
| Base unit | ESPRIMO D6012 ESPRIMO D6012 ESTAR | |
| Power consumption | | |
| Power consumption note | See white paper Energy Consumption | |
| Noise emission | | |
| Related Processors for noise | Intel® Core™ i5-12500 processor and 8GB, ODD; Windows 11 (tower position) | |
| Standard noise emission | According to ISO 7779:2010, ECMA-74 | |
| itandard noise notes / description | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) | |
| Standard noise operation mode: CPU 50% load | Bystander; Operator position PLATINUM PSU: 3.3 B / 19 dB(A); 22 dB(A) (SSD M.2) GOLD PSU: 3.4 B / 21 dB(A); 22 dB(A) (3.5" HDD) | |
| Standard noise operation mode: HDD oad | Bystander; Operator position PLATINUM PSU: 3.3 B / 20 dB(A); 22 dB(A) (SSD M.2) GOLD PSU: 3.5 B / 22 dB(A); 24 dB(A) (3.5" HDD) | |
| Standard noise operation mode: Idle node | Bystander; Operator position PLATINUM PSU: 3.3 B / 20 dB(A); 22 dB(A) (SSD M.2) GOLD PSU: 3.4 B / 21 dB(A); 22 dB(A) (3.5" HDD) | |
| Standard noise operation mode: ODD oad | Bystander; Operator position PLATINUM PSU: 4.5 B / 32 dB(A); 36 dB(A) (SSD M.2) GOLD PSU: 4.7 B / 33 dB(A); 37 dB(A) (3.5" HDD) | |
| Standard noise operation mode: Office applications 2.0 | Bystander; Operator position PLATINUM PSU: 3.3 B / 20 dB(A); 22 dB(A) (SSD M.2) GOLD PSU: 3.4 B / 21 dB(A); 22 dB(A) (3.5" HDD) | |
| Dimensions / Weight / Environmental | | |
| Dimensions (W x D x H) | 314 x 296 x 89 mm | |
| | 12.36 x 11.65 x 3.51 inch | |
| | | |

| Dimensions / Weight / Environmental | | |
|-------------------------------------|--|--|
| Weight | Min: 5.7kg; 1x mem, 1xSDD Max: 6.0kg; | |
| | power cord (0.2kg) is not part of min/max | |
| Weight (lbs) | approx. 17.64 lbs | |
| Weight notes | Actual weight may vary depending on configuration | |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F) | |
| Operating relative humidity | 5 - 85 % (relative humidity) | |
| Compliance | | |
| Product | ESPRIMO D6012 | ESPRIMO D6012 ESTAR |
| Model | DTG | |
| Germany | GS TÜV NRTL | |
| Europe | CE | |
| Global | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 8.0 EPEAT® Gold (dedicated regions) TCO Certified, generation 9 |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates | |
| Additional Software | | |
| Additional software (preinstalled) | McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre- installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.) | |
| Additional software (optional) | Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero Essentials XL Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office. Purchase and activation only in the region in which was acquired.) | |
| Additional software (notes) | Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration. | |
| Base unit | ESPRIMO D6012 | ESPRIMO D6012 ESTAR |
| Security | | |
| Physical Security | Kensington Lock support Eye for padlock Integrated cabinet lock (optional) Cable Cover (optional; covers and secures the ports and c | ables on rear side) |
| System and BIOS Security | Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby (Windows 11 only) and Legacy Standby selectable Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces NIST SP800-147 BIOS Protection supported NIST SP800-155 BIOS Integrity Measurement supported NIST SP800-193 Platform Firmware Resiliency supported | |
| User Security | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optiona | 1) |

| Security | | |
|---|---|--|
| Security Notes | The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation. | |
| Manageability | | |
| Manageability technology | DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) | |
| Manageability software | DeskView Client DeskView Instant BIOS Management | |
| DeskView components | BIOS Management incl. Security Inventory Management Driver Management Alarm Management | |
| Supported standards | DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model) | |
| Manageability link | https://www.fujitsu.com/global/products/computing/pc/manageability/ | |
| Miscellaneous | | |
| | Keyboard on with one key (Fujitsu Keyboards KB521, KB955) Keyboard on with two keys (CTRL+CTRL; special Fujitsu USB keyboards required) Keyboard on with any key (USB) Thermal management Internal dust filter (optional) | |
| Packaging information | | |
| Packaging dimension (mm) | 499 x 296 x 439 mm | |
| Packaging dimension (inch) | 19.65 x 11.65 x 17.28 inch | |
| Max. quantity / pallet | 24 | |
| Material - Weight (g) Carton | 1114 g | |
| Material - Weight (lbs) Carton | 2.46 lbs | |
| Material - Weight (g) PE | 263 g | |
| Material - Weight (lbs) PE | 0.58 lbs | |
| Packaging notes | printed user documentation is bleached in chlorine free process; Bulk packaging for projects (optional) | |
| Warranty | | |
| Warranty period | 1 year | |
| Warranty type | Bring-In / Onsite Service (depending on country) | |
| Warranty Terms & Conditions | http://www.fujitsu.com/warranty | |
| Digital bug fixes | Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer. | |
| Product Support - the perfect extension | | |
| Recommended Service | 9x5, Onsite Response Time: Next Business Day | |
| Spare Parts availability | 5 years | |
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support-services/ | |

Recommended Accessories

Blue LED Mouse M960



The Blue LED Mouse M960 comes in a slim design with proven Fujitsu engineering quality. The track on glass Blue LED sensor enables ultra precise switchable resolution at 1,000, 1,600 and 2,000 dpi. Blue LED Mouse M960 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.

Order Code: S26381-K470-L100

More information

Fujitsu products, solutions & services

In addition to Fujitsu Desktop ESPRIMO D6012, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Desktop ESPRIMO D6012, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/emeia/products/

computing/pc/desktops/

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/ global/about/resources/terms/ Copyright 2024 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2024-04-06 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/ Copyright 2024 Fujitsu Technology Solutions GmbH