Fujitsu recommends Windows 11 Pro.

FUJITSU

Data Sheet Fujitsu Desktop ESPRIMO G6012

Mini, Mighty | Takes up your challenges, not your space

The Fujitsu ESPRIMO G6012 is a stylish Mini PC which offers desktop functionality in an ultracompact, space-saving design. The Intel vPro[®] with 12th Gen Intel[®] Core[™] processors provides the performance for daily office needs. Flexible mounting options like attach to displays, wall mount, under table mount, its size and many interfaces make it to an ideal device where space saving is critical.

A stylish Mini PC with ultra-compact design

- Energy and space-saving for clean, clutter-free desk with convenient access to ports and ODD
- Fully equipped PC with a volume of only ~0.87 liters
- Impressive performance/volume ratio and is easy to set up in minutes
- Benefit of DVD- and Bluray drive option in a slightly bigger chassis

Ultimate usability

Flexible mounting and wide range of usage scenarios

- Can be used for horizontal or vertical operations and easy upgrade of major components
- Best prepared for VESA mount usage
- Integrate ESPRIMO G6012 into Fujitsu AIO Display P2410 for space saving and flexible upgrades

Small yet grand

High performance in a small Mini PC design

- Intel[®] chipset technology and 12th Generation Intel[®] Core[™] processor family
- Legacy support for standard Mini PC interfaces

Perfect fit for modern offices and workplaces of tomorrow

The PC which can transform your workplace for the next generation

- Supports new workplace scenarios with a single Type-C connection
- Type-C Docking port for future workplace and AiO-like usage

Feature-rich and energy-efficient

Do a lot more with this Mini PC and also get lesser energy bill

- Improved energy efficiency
- Next generation INTEL integrated graphics
- Type-C connector with front access to support peripherals like Type-C USB sticks or headsets
- High efficient AC adapter or be operated by the power from peripherals, e.g. port rep or displays
- Sum of post-consumer recycled content for plastic per weight is up to 50% (min. 11% are from ITE derived post-consumer material and min. 35% are any other post-consumer material)







Components

	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
Processor			
	*with Intel® Turbo Boost Technology 2.0 (clock speed and p variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed other variables)		
Operating systems			
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home Windows 10 Pro. Fujitsu recommends Windows 11 Pro for business.		
Operating system compatible	Certified for Red Hat© Enterprise Linux		
Operating system notes	 Windows 11 requires for first device setup: Internet connectivity Microsoft account for Home editions or organizational account (e.g. ADD) for Pro editions After product end of life, Fujitsu continues to test and support new Windows releases for max. 5 years, depe extension of hardware services through warranty top ups. For more details please visit our Fujitsu Service Statement under https://support.ts.fujitsu.com/IndexProdSu asp?lng=com&OpenTab= The use of Windows Operating System is subject to acceptance of the End User License Agreement of Micro applicable under the relevant Microsoft program. 		
	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
Memory modules			
	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive) 2.5-inch bay for devices with 7mm height Durability in accordance with the manufacturer's indications on read and write cycles.		
	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
Optical drive			
	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
LAN Notes	WI-FI 6E: The device does not operate in 6GHz band in all countries, due to national regulations. see flexible interface options Bluetooth 5.2: Bluetooth® 5.2 operation requires Microsoft OS support. Until Microsoft OS support is availab Bluetooth® 5.2 will function as Bluetooth® 5.1 or lower		
	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
Component notes	The listed product components and optional functions are not available in all region/countries; System is available in 2 different housing versions: Small version (0.87 Liter) ODD bay version (1.23 Liter)	The listed product components and optional functions as not available in all region/countries; Energy Star certification only with Windows operating system Base unit for TCO Certified generation 9;	
		System is available in 2 different housing versions: Small version (0.87 Liter) ODD bay version (1.23 Liter)	

Base unit

Base unit	ESPRIMO G6012	ESPRIMO G6012 ESTAR
Mainboard		
Mainboard type	D4014-B	
Formfactor	proprietary	
Chipset	Intel® B660	
Processor socket	LGA1700	
Processor quantity maximum	1	
Supported capacity RAM (max.)	64 GB	
Memory slots	2 DIMM (DDR4)	
Memory frequency	3,200 MT/s	
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to 3200 MT/s may be clocked down to 2933/2400 MT/s depen	
LAN	10/100/1,000 MBit/s Intel® I219V	
Integrated WLAN	optional	
BIOS version	AMI Aptio V UEFI Specification 2.8	
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)	
Audio type	On board	
Audio codec	Realtek ALC257N	
Audio features	Internal speaker supports audio playback, High Definition a	audio
I/O controller on board		
Serial ATA total	2	
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI	
Interfaces		
Front audio: headset	1	1
Flexible Interface Options	One of following flexible Interface options can be added to the system HDMI [™] (supports 4k@60Hz as specified in HDMI [™] 2.1) DisplayPort [™] 1.4a (external HDMI- and DVI adapters not supported) 2.5 Gigabit Ethernet (Intel 225LM) Serial port (9pin, 16 byte FIFO, 16550 compatible) 2x USB 2.0 Type A	One of following flexible Interface options can be added to the system HDMI™ (supports 4k@60Hz as specified in HDMI™ 2.1) DisplayPort™ 1.4a (external HDMI- and DVI adapters not supported) Serial port (9pin, 16 byte FIFO, 16550 compatible) 2x USB 2.0 Type A
USB front	1x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-C (provides up to 15W)	1x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-C (provides up to 15W)
USB rear	2x USB 2.0 Type-A 1x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 Type-C (10 Gbps, supports DisplayPort 1.4 and power delivery sink **) see flexible interface options	2x USB 2.0 Type-A 1x USB 3.2 Gen 1 (5 Gbps) Type-A 1x USB 3.2 Gen 2 (10 Gbps) Type-A 1x USB 3.2 Gen 2 Type-C (10 Gbps, supports DisplayPort 1.4 and power delivery sink **) see flexible interface options
DisplayPort	1 (DisplayPort 1.4; DP++)	1 (DisplayPort 1.4; DP++)
HDMI	1 - Supports 4K@60Hz as specified in HDMI [™] 2.1	1 - Supports 4K@60Hz as specified in HDMI™ 2.1
Ethernet (RJ-45)	1	1
Interface Module notes	**With power delivery sink support, the system is operated by the power from peripherals, e.g. port replicators or displays. An extra power supply for the system is not needed. Peripherals must provide min. 60Watt or 90Watt (for maximum CPU performance).	**With power delivery sink support, the system is operated by the power from peripherals, e.g. port replicators or displays. An extra power supply for the system is not needed. Peripherals must provide min. 60Watt or 90Watt (for maximum CPU performance).
Kensington Lock support	(for maximum CPU performance).	(for maximum CPU performance).

Input device / components		
Input devices (optional)	Keyboard	
	Mouse	
Drive bays		
Drive bays total	2	
2.5-inch internal bays	1	
5.25-inch external bays	1	
Drive bay notes	5.25" bay: for slim optical disc drive only as	
M.2-2280	1 x on mainboard (PCle 4.0 x4; up to 64Gbi	t/s) and 1 x optional (PCIe 3.0 x4; up to 32Gbit/s)
Mini PCI slots		
M.2-2230	on mainboard for WLAN module	
Graphics on board		
Graphics brand name	Intel® UHD Graphics 770, Intel® UHD Graph	ics 730, Intel® UHD Graphics 710
Shared video memory	Up to half size of total system memory	
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel	
TFT resolution (HDMI)	Up to 4,096 x 2,304 pixel	
Graphics features	Support for up to four independent display DirectX® 12.1 HDCP support OpenCL 3.0 OpenGL ® 4.6 Vulkan™ DisplayPort interface supports Ver. 1.4 incl. Digital audio formats are supported, includ see flexible interface options	Multi-Stream
Base unit	ESPRIMO G6012	ESPRIMO G6012 ESTAR
Electrical values		
Power efficiency note	90 Watt AC adapter: power supply efficience	v at 115/230V: 89% average efficiency
Rated voltage range	100 V - 240 V	,
Rated frequency range	50 Hz - 60 Hz	
Operating voltage range	90 V - 264 V	
Operating line frequency range	47 Hz - 63 Hz	
Max. output of single power supply	AC Adapter: 90 W	
Base unit	ESPRIMO G6012	ESPRIMO G6012 ESTAR
Power consumption		
Power consumption note	See white paper Energy Consumption	
Noise emission		
Related Processors for noise	Intel [®] Core™ i5-12500T processor and	
Related Processors for hoise	8GB, no ODD, Windows 11 (tower position)	
Standard noise emission	According to ISO 7779:2010, ECMA-74	
Standard noise notes / description		/ Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.0 B / 17 dB(A) Bystander; 18 dB(A) Operat	
Standard noise operation mode: HDD	3.2 B / 19 dB(A) Bystander; 21 dB(A) Operat	or position (SSD M.2)
load	· · ·	
Standard noise operation mode: Idle mode	3.0 B / 17 dB(A) Bystander; 17 dB(A) Operat	or position (SSD M.2)
Standard noise operation mode: Office applications 2.0		
Dimensions / Weight / Environmental		
	146 5 - 164 5 - 26	
Dimensions (W x D x H)	146.5 x 164.5 x 36 mm	

Dimensions / Weight / Environmenta			
Dimension notes	With ODD drive bay, the dimensions are: 146.5 x 164.5 x 51 mm (5.77 x 6.48 x 2.01 inch)		
Operating position	Vertical / horizontal (feet included)		
Weight	Small: Min:0.85kg; 1x mem.,1x SDD Max:1.015kg; 2x mem.,2x SSD,HDD,Flexi,WLAN ODD version: Min:1.185kg / Max:1.275kg AC adapter (0.32kg) and power cord 0.175kg) are not part of min/max		
Weight (lbs)	Small: Min: 1.88 lbs / Max: 2.24 lbs ODD version: Min:2.62 lbs / Max:2.82 lbs AC adapter (0.71 lbs) and power cord 0.39 lbs) are not par	t of min/max lbs	
Weight notes	Actual weight may vary depending on configuration		
Operating ambient temperature	10 - 35 °C (50 - 95 °F)		
Operating relative humidity	5 - 85 % (relative humidity)		
Compliance			
Product	ESPRIMO G6012	ESPRIMO G6012 ESTAR1	
Model	MPCG		
Germany	GS TÜV NRTL		
Europe	CE		
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 8.0 EPEAT® Gold (dedicated regions) TCO Certified, generation 9	
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	-	
Additional Software			
Additional software (preinstalled)	McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre- installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)		
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero Essentials XL Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021	ft Office. Purchase and activation only in the region in which i	
Additional software (notes)	Use of accompanying and/or additional Software is subjected and support terms of the Software whether preinstalled or optional. The software may be subscription which – depending on the Software - may be	he Software manufacturer as applicable for the relevant nay only be available bundled with a software support	
Base unit	ESPRIMO G6012	ESPRIMO G6012 ESTAR	
Security			
Physical Security	Kensington Lock support Eye for padlock		
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requi Modern Standby (Windows 11 only) and Legacy Standby Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces NIST SP800-147 BIOS Protection supported NIST SP800-155 BIOS Integrity Measurement supported NIST SP800-193 Platform Firmware Resiliency supported		

Security		
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) The properties of the product provide a baseline for product security and therefore end-customer IT security. Howeve these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuratic options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.	
Security Notes		
Manageability		
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)	
Manageability software	DeskView Client DeskView Instant BIOS Management	
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management	
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)	
Manageability link	https://www.fujitsu.com/global/products/computing/pc/manageability/	
Miscellaneous		
	Keyboard on with one key (Fujitsu Keyboards KB521, KB955) Keyboard on with two keys (CTRL+CTRL; special Fujitsu USB keyboards required) Keyboard on with any key (USB) Thermal management	
Accessories information	Further helpful options Desktop Accessories: http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/	
	http://www.fujitsu.com/global/products/computing/peripheral/accessories/connectivity/ Stands and Mounting kits: http://www.fujitsu.com/global/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf	
Packaging information		
Packaging dimension (mm)	395 x 198 x 284 mm	
Packaging dimension (inch)	15.55 x 7.8 x 11.18 inch	
Max. quantity / pallet	42	
Material - Weight (g) Carton	1025 g	
Material - Weight (lbs) Carton	2.26 lbs	
Material - Weight (g) PE	15 g	
Material - Weight (lbs) PE	0.03 lbs	
Packaging notes	If keyboard is included in packaging: 1.)packaging dimension is increasing to: 497 x 206 x 293mm / (19.6 x 8.11 x 11.5 inch); 2.) material weight is increasing to: carton 1025g, PE 15g printed user documentation is bleached in chlorin free process;	
	Bulk packaging for projects (optional)	
Warranty		

Warranty		
Warranty type	Bring-In / Onsite Service (depending on country)	
Warranty Terms & Conditions	http://www.fujitsu.com/warranty	
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.	
Product Support - the perfect extension		
Recommended Service	9x5, Onsite Response Time: Next Business Day	
Service Lifecycle	5 years	
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/	

Recommended Accessories

Mounting Kit for Height Adjustable Fujitsu Displays - up to 11th Gen. Display (2022)	The Fujitsu Mounting Kit for Height Adjustable Fujitsu Displays has been specifically (2022) designed for use with ESPRIMO Q/G Mini PCs, FUTRO Thin Clients and Fujitsu Displays. With this solution you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.	Order Code: FPCSK834GP
Mounting Kit for Height Adjustable Fujitsu Displays - up to 10th Gen. Display	The Fujitsu Mounting Kit for Height Adjustable Fujitsu Displays has been specifically designed for use with ESPRIMO Q/G Mini PCs, FUTRO Thin Clients and Fujitsu Displays. With this solution you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.	Order Code: S26361-F2542-L452
Universal Monitor Stand	Save desk space without compromising productivity with the Universal Monitor Stand that brings together a Desktop ESPRIMO Mini PC (G Series Small and ODD plus Q Series) or Thin Client FUTRO and a VESA compatible Fujitsu Display. For optimum ergonomics the height and tilt angle of the display can be adjusted, whilst hassle-free installation of the devices on the stand makes the life of your IT department easier.	Order Code: S26361-F2601-L700
		Order Code:

S26381-K473-L100

More information

Fujitsu products, solutions & services

In addition to Fujitsu Desktop ESPRIMO G6012, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Desktop ESPRIMO G6012, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/emeia/products/

computing/pc/desktops/

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/ global/about/resources/terms/ Copyright 2024 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2024-04-06 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see https://www.fujitsu.com/global/about/resources/terms/ Copyright 2024 Fujitsu Technology Solutions GmbH