

Data Sheet

Fujitsu Thin Client FUTRO S7011

Ultra-compact and Powerful Thin Client

The FUTRO S7011 is an ultra-compact and powerful Thin Client device for companies that need flexible end-points with an optimal mix of industry leading OS, Thin Client device management consoles and flexible hardware options helping you provide secure client cloud computing and full productivity choices for your employees

Improved performance with advanced technology

Ultimate performance to meet the business challenges of future computing

- AMD Ryzen™ Embedded R1505G processors & fast NVM Storage technology
- Fanless, zero noise Thin Client with dual channel memory support

eLux RP 6 Thin Client OS and Scout Enterprise Management Suite® 15

Enables upfront cost savings and keeps your IT infrastructure secure, up-to-date with continuous security patch releases

- Unicon offers a flexible licensing model that offers the eLux OS and Scout Enterprise Management Suite including Cloud Gateway with long term support for the latest updates

Enterprise-grade security

Enables you to provide a secure end-point device that helps prevent unauthorized access to sensitive enterprise data

- Centralized administration and granular access controls coupled with built-in BIOS security, Write Filter Protection and Kensington lock support

Ultra-compact design with improved connectivity

Be flexible and stay productive in a hyper-connected world

- Fully equipped Thin Client with a volume of only ~0.86 liters
- USB Speed up to 10Gbps
- Up to 7 USB Ports with 3 USB Type-C ports, variety of different display connectors

Full productivity

The PC which will transform your workplace for the next gen needs

- UC&C ready with multi-monitor support for up to three displays and ideal mix of modern (Type-C) and legacy interfaces
- Run the system with just one single USB-C cable for a clean desk



Technical details Components

Memory modules	4 GB (1 module(s) 4 GB) DDR4, 2,400 MT/s, SO DIMM 8 GB (1 module(s) 8 GB) DDR4, 2,400 MT/s, SO DIMM
Graphics	DP to DVI-D (single link) Adapter Cable Display Port to VGA Adapter
Storage (internal)	SSD PCIe, 128 GB NVMe, M.2 module, Flash drive (TLC technology), 75 TBW* SSD PCIe, 64 GB (57GB useable) NVMe , M.2 module, Flash drive (TLC technology), 39 TBW*
Storage notes	Important Notice for M.2 Module Use: Predefined by NAND-Flash-Technology the device only supports a defined maximum number of Terabytes written. Any and all warranty for such devices is limited to this maximum Terabytes written. Please notice the section "restricted warranty" in our warranty book. Fujitsu therefore strongly recommends to activate the write filter of the M.2 module once the configuration is finished. This activation ensures the durability of the flash module and is also mandatory to ensure a highest level of IT security (e.g. against virus attacks). In case of a need to enable further write cycles the write filter can then be deactivated again at any time. *Terabytes written (TBW) calculated based on JESD-219A SSD Client workload One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
Interface add on cards/components (optional)	Internal speaker Serial Port
Base unit	FUTRO S7011
Operating system and software (Linux)	
Operating system	eLux® RP
Notes	eLux® is a hardware-independent operating system for cloud computing environments. eLux ensures hardware independence and migration ability. An existing license can simply be transferred via Scout Enterprise whenever the hardware is upgraded. New updates and upgrades are always built modular – only the changed parts (delta) of the software are transferred to the device and implemented into the existing installation. Software updates and upgrades are available around the clock at myelux.com.
Functions	eLux® RP 6 Citrix Receiver VMware® Horizon Client Updates and optional software packages are available at www.myelux.com
Manageability	Scout Enterprise, flash memory management, embedded operating system update and system monitoring, managing devices by location, group or user, individual operating system composition with ELIAS (eLux and Scout Enterprise Management Suite license required)
Operating system and software (Windows 10 IoT)	
Operating system	Windows® 10 IoT Enterprise 2021 LTSC
Notes	Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support.ts.fujitsu.com .
Functions	Internet Explorer Citrix Receiver VMware® Horizon Client
Security software	
Additional software (notes)	Use of accompanying and/or additional Software is subject to proactive acceptance of the respective License Agreements /EULAs/ Subscription and support terms of the Software manufacturer as applicable for the relevant Software whether preinstalled or optional. The software may only be available bundled with a software support subscription which – depending on the Software - may be subject to separate remuneration.
Mainboard	
Mainboard type	D3944-A1

Mainboard

Processor	AMD Ryzen™ Embedded R1000 Series R1505G (Dual Core, 2.4 GHz, up to 3.3 GHz, AMD Radeon™ Vega 3 Graphics) (,)
Memory slots	2 SO DIMM (DDR4, 2400 MHz)
Supported capacity RAM (max.)	16 GB
Memory notes	For dual channel performance and full graphics support, 2 memory modules have to be ordered
LAN	Built-in 10/100/1,000 MBit/s Realtek RTL8111H
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC623
Mini PCI slots	
PCI-Express 3.0 x1 (mech. x4) length inch	6.61 inch
PCI-Express 3.0 x1 (mech. x4) length mm	168 mm

Interfaces

DC-in	1
Front audio: headphone	1
USB 2.0 total	3
USB 3.2 Gen2 (10 Gbps) total	3
USB front	1x USB 3.2 Gen 2 1x USB 3.2 Gen 2 Type-C
USB rear	1x USB 3.2 Gen 2 Type-C + 1 (optional*, supports DisplayPort and power delivery sink support e.g. from a display) 3x USB 2.0
USB internal	1 pin header
DisplayPort	2 (DisplayPort 1.4) + 1 (optional*)
Serial (RS-232)	1 (optional) + 1 (optional*)
HDMI	1 (optional*)
Ethernet (RJ-45)	1 + 1 (optional* 2.5GB LAN)
Interface Module notes	*only one "optional" interface can be configured at the same time.
Kensington Lock support	1

Graphics on board

Graphics brand name	AMD Radeon™ Vega 3 Graphics
Graphics color depth	32 bit colors
TFT resolution (DisplayPort)	up to 4,096 x 2,160 @ 60 Hz
Graphics features	DirectX® 12 OpenGL® 4.6 Vulkan™ Open CL® 2.2
Graphics notes	Graphics resolution and performance depends on operating system and infrastructure environment. It is strongly recommended to test and validate the target use case.

Electrical values

Power consumption long idle	5.99 W
Power consumption sleep mode power	1.62W (WoL disabled)
Power consumption off mode power	0.27 W (WoL disabled)
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	100 V - 240 V (AC Input)
Operating line frequency range	50 Hz - 60 Hz

Dimensions / Weight / Environmental

Dimension with stand (W x D x H)	68 x 165 x 156 mm
Dimensions (W x D x H)	36 x 165 x 147 mm
Operating position	Vertical / horizontal

Dimensions / Weight / Environmental

Weight	min: 624 g (1 x memory, 1x SSD, w/o AC-Adapter) max: 664 g (full expansion, w/o AC-Adapter) AC-Adapter + power cord: 277 g
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	FUTRO S7011
Model	TCS6
Germany	GS
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Security

Physical Security	Kensington Lock support
System and BIOS Security	Trusted Platform Module (TPM 2.0), optional without TPM User and supervisor BIOS password
Security Notes	The properties of the product provide a baseline for product security and therefore end-customer IT security. However, these properties are not sufficient on their own to protect the product from all existing threats, such as intrusion attempts, data exfiltration and other forms of cyberattacks. To customize security settings, please use the configuration options as available for the respective product. During operation, the IT security of this product is within the responsibility of the respective administrator/end-user of the product. Please note, that Fujitsu as a manufacturer does not make any policy prescriptions or advocacy statements regarding IT security best practices and/or general product operation.

Packaging information

Packaging dimension (mm)	395 x 197 x 288 mm
Packaging dimension (inch)	15.55 x 7.76 x 11.34 inch
Max. quantity / pallet	84
Material - Weight (g) Carton	698 g
Material - Weight (lbs) Carton	1.54 lbs
Material - Weight (g) EPS / PS	0 g
Material - Weight (lbs) EPS / PS	0 lbs
Material - Weight (g) PE	20 g
Material - Weight (lbs) PE	0.04 lbs
Packaging notes	If keyboard is included in packaging, dimension is increasing to: 497 x 206 x 293 mm and material weight of carton will increase to 901 g

Warranty

Warranty period	2 years (depending on country)
Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://www.fujitsu.com/warranty
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.

Product Support - the perfect extension

Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	at least 5 years after shipment, for details see https://support.ts.fujitsu.com/
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

Recommended Accessories

Mounting Kit for Height Adjustable Fujitsu Displays - up to 10th Gen. Display



The Fujitsu Mounting Kit for Height Adjustable Fujitsu Displays has been specifically designed for use with ESPRIMO Q/G Mini PCs, FUTRO Thin Clients and Fujitsu Displays. With this solution you can save space on the desk, reduce clutter on desk and realize a clean desk working environment.

Order Code:
FPCSK740GP

Mouse M520 black



The Fujitsu Accessory Mouse M520 black is an essential input device for PCs that works on nearly every surface and follows your hand movements smoothly and precisely. It features two buttons and a scroll wheel which also can be used as third button.

Order Code:
S26381-K467-L100

Mouse M520 grey



The Fujitsu Accessory Mouse M520 grey is an essential input device for PCs that works on nearly every surface and follows your hand movements smoothly and precisely. It features two buttons and a scroll wheel which also can be used as third button.

Order Code:
S26381-K467-L101

More information

Fujitsu products, solutions & services

In addition to Fujitsu Thin Client FUTRO S7011, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu Thin Client FUTRO S7011, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/emeia/FUTRO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. The overall product has been designed and manufactured for general office use, regular personal use and ordinary industrial use.

Contact

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com
2022-12-02 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>
Copyright 2020 Fujitsu Technology Solutions GmbH